

HYPHONE

www.hyphone.com.tw

INTRODUCTION



Wheel not included

Model No. HY-1046


Air Tire Buffer

Best In Class

- ◆ 0.5 Horsepower @ 2600RPM
- ◆ Max. torque @ 57.5 in-lb (6.5 Nm)
(10X as grinder @20,000 rpm)
- ◆ Built in speed regulator
- ◆ Thermal protective housing cover
- ◆ Rear exhaust with special ultra quiet muffler 83 dBA
- ◆ Comfortable Safety throttle
- ◆ Triple planetary steel alloy gearing in steel nose case
- ◆ Includes buffing wheel adapter

Max Free Speed RPM	2,600 rpm
Quick change Chuck	11 mm
Max. Torque output in-lb / Nm	57.5 / 6.5
Weight lb/kg	2.33 lb / 1.06 Kg
Length in/mm	8.66" / 220 mm
Average air consumption cfm/L min	3.66 cfm / 107 L/min
Sound pressure power dBA	83 / 94 dBA
Air inlet in.	1/4"
Minimum hose size in/mm.	3/8" / 10 mm

✓ Optional
whip and exhaust hose kit
**Special muffler without
reducing torque**



Hyphone Machine Industry

TEL:886-4-2563-3678

21, Lane 742, Sec 1, He-Mu Rd. Shen Gang Dist.
Taichung, Taiwan